

Cisco® Compatible CWDM SFPs, 1490nm



[Back to SFP Page](#)

<b>CWDM-SFP-1490:</b>	<b>FDN-CWDM-SFP-1490-nm</b>
<b>Cisco® Compliant Ethernet Transceiver</b>	
<b>1.25GB Gigabit Ethernet / 1.063GB Fiber Channel</b>	
<b>Application:</b> This 100% Cisco® Compliant 1000Base CWDM SFP Transceiver is hot-swappable and designed to plug directly into your SFP/Mini-GBIC interface slot in your router and switch for CWDM Ethernet and Fiber Channel network interface applications.	
Reach	70km
Fiber Type	SMF Singlemode Fiber
Fiber Optic Connector	LC
Center Wavelength	1490nm
Min TX Power	0 dBm
Max TX Power	5 dBm
RX Sensitivity	-23 dBm
Max Input Power	-3 dBm
Link Budget	23 dB
Dimensions	MSA SFP Standard Height: 0.33" (8.5 mm) Width: 0.52" (13.4 mm) Depth: 2.18" (55.5 mm)
Power	3.3V
Operating Temperature	0°C - 70°C
Standards	IEEE: 802.3 2003; ANSI X3.297-1997
Compliance	IEC-60825; FDA-21; CFR 1040.10 CFR 1040.11
Warranty	1 Year Full Replacement

Cisco® is a registered trademark of Cisco Systems, Inc.