

[Back to GBICs](#)

WS-G5486:	FDN-WS-G5486
Cisco® Compliant Ethernet Transceiver	
1.25GB Gigabit Ethernet / 1.063GB Fiber Channel	
Application: This 100% Cisco® Compliant 1000Base GBIC Gigabit Transceiver is hot-swappable and designed to plug directly into your SFP/GBIC interface slot in your router and switch for Ethernet and Fiber Channel network interface applications.	
Reach	10km
Fiber Type	SMF (Singlemode Fiber)
Fiber Optic Connector	SC
Center Wavelength	1310nm
Min TX Power	-9.5 dBm
Max TX Power	-3 dBm
RX Sensitivity	-20 dBm
Max Input Power	-3 dBm
Link Budget	10.50 dB
Dimensions	MSA SFP Standard Height: 1.40" (10 mm) Width: 1.20" (30 mm) Depth: 2.60" (65 mm)
Power	3.3V
Operating Temperature	0°C - 70°C
Standards	IEEE: 802.3 2003; ANSI X3.297-1997
Compliance	IEC-60825; FDA-21; CFR 1040.10; CFR 1040.11
Warranty	1 Year Full Replacement

Cisco® Part Number	Fiberdyne Part Number	Description
WS-G5486	FDN-WS-G5486	Cisco® Compliant 1000Base-LX/LH GBIC 1310nm Dual SC 10km, SMF