# FIBERDYNE LABS, INC.

#### **Wall Mount Fiber Splice Enclosure**



| ITEM NO. | QTY. | PART NO.   | DESCRIPTION                                 |
|----------|------|------------|---|
| 1        | 1    | 744-567-P1 | TROUGH BK FWM054X                           |
| 2        | 1    | 591-381-P1 | DOOR LT BK FWM054X                          |
| 3        | 1    | 591-382-P1 | DOOR RT BK FWM054X                          |
| 4        | 4    | 591-384-P1 | PLATE CAPPLUG BK (2X 1 1/8")                |
| 5        | 4    | 591-385-P1 | BRACKET STRAIN RELIEF BK FWM054X            |
| 6        | 2    | 591-386-10 | HINGE ROD 16 7/8"                           |
| 7        | 2    | 12025      | LATCH, BLACK, SERIES 40, A3-40-625-12       |
| 8        | 2    | 99534      | LOCK & KEYS CAM N23058 SF                   |
| 9        | 8    | 99910      | GROMMET, 1.125"                             |
| 10       | 4    | 10-3621    | ICCMFRMU02 FIBER RADIUS MANAGEMENT BRKT     |
| 11       | 32   | 630-116-10 | STUD PEM 8-32 X 3/8 ZI                      |
| 12       | 32   | 634-010-10 | NUT 8-32 K-LOCK ZI                          |
| 13       | 1    | 10-4547    | KIT HARDWARE FWM054X W/ 2 KEYS              |
| 14       | 1    | 99018      | CARTON FWM054X PLAIN RSC                    |
| 15       | 1    | 744-574-20 | SPLICE TRAY RACK ASSY FWE288XH              |
| 16       | 11   | 591-410-10 | SPLICE TRAY RACK SHELF FWE288XH             |
| 17       | 4    | 630-060-10 | STUD PEM 10-32 X 3/8 ZI                     |
| 18       | 4    | 634-011-10 | NUT 10-32 K-LOCK ZI                         |
| 19       | 8    | 10-3622    | WASHER FLAT NYLON BLACK (.625 X .25 X .062) |

#### Introduction:

The Fiberdyne *WDL288* is an indoor wall mount fiber splice enclosure with the capacity to splice 288 single fusion splices. The enclosure features 12 slots to hold up splice trays designed for up to 24 splices and 4 storage spools for cable slack. The enclosure has multiple cable entry ports on the top and bottom with cable tie down points to secure installed fiber cables. The enclosure features 2 doors with locks that open independently.


#### **General Specifications:**


| Dimensions:   | 17" H x 21.2" W x 5" D           |
|---------------|----------------------------------|
| Splice Trays: | (12) FST-2020-SS*                |
| Material:     | 16 Gauge Steel Black Powder Coat |

\*Ordered Separately

#### **Ordering Information:**

| Part Number | Description                                     |
|-------------|---|
| WDL288      | Fiberdyne Wall Mount Splice Enclosure           |
| FST-2020-SS | Fiberdyne Splice Tray, 24 Single Fusion Splices |





### (800) 894-9694

## **/** FIBERDYNE LABS, INC.

Sales@fiberdyne.com