



[Back to SFP Page](#)

SFP-GE-L :	FDN-SFP-GE-L SFP
Cisco® Compliant Ethernet Transceiver	
1.25GB Gigabit Ethernet / 1.063GB Fiber Channel	
Application: This 100% Cisco® Compliant 1000Base LX/LH SFP 1310nm Transceiver with DOM and extended temperature, is hot-swappable and designed to plug directly into your SFP/Mini-GBIC interface slot in your router and switch for Ethernet and Fiber Channel network interface applications.	
Reach	10-20km
Fiber Type	SMF
Fiber Optic Connector	LC
Center Wavelength	1310nm
Min TX Power	-9 dBm
Max TX Power	-3 dBm
RX Sensitivity	-23 dBm
Max Input Power	-3 dBm
Link Budget	14 dB
Dimensions	MSA SFP Standard Height: 0.33" (8.5 mm) Width: 0.52" (13.4 mm) Depth: 2.18" (55.5 mm)
Power	3.3V
Operating Temperature	-5°C - 85°C Extended Range: -20 - 85°C
Standards	IEEE: 802.3 2003; ANSI X3.297-1997
Compliance	IEC-60825; FDA-21; CFR 1040.10; CFR 1040.11
Warranty	1 Year Full Replacement

Cisco® is a registered trademark of Cisco Systems, Inc.